



QM-4100-4K

4K60 HDMI®, 4 HDMI® input
with 1 HDMI® output seamless
switch

Features

- Uncompressed 4K/60Hz 4:4:4
- 4 inputs and 1 outputs for 4x1 presentation switching applications
- Seamless switching between multiple sources to single output
- Up/down scaling from 1080p to 4K60
- Flexible control via IR (remote control), front push buttons, RS232, and API (Application Programming Interface)



front

QM-4100-4K is a seamless-switcher for uncompressed 4K/60Hz with 4 HDMI® 2.0 inputs and 1 HDMI® 2.0 output. High performance provides presenters the ability to share content effectively on a single display and switch any input to a single output with out limits. Additionally, each HDMI® input has ability to de-embedded audio. QM-4100-4K can be controlled in a variety of ways: RS-232, front panel buttons and IR. It can be used for numerous applications such as corporate/enterprise, education, healthcare, government, military command and control and much more!



back



Video Specifications	
Input/output	4x HDMI® 2.0 inputs 1x HDMI® 2.0 outputs
Input/Output Resolution	4K60, 4:4:4
HDCP	2.2
Audio Specifications	
Output	Embedded HDMI
Connector	HDMI

Control Specifications	
Interfaces	IR, Front Push Buttons, RS-232, and API
Connectors	DB-9 (RS-232)

Mechanical Specifications	
Enclosure	Stand-alone
Dimensions	9.96" x 5.47" x 1.57"
Weight	1.87 lbs
Power Specifications	
Power Supply	12VDC@2A
Environmental Specifications	
Operating Temp	0 to 50C
Storage Temp	-40 to 80C



Models	Description
QM-4100-4K	4K60 4x1 presentation/seamless switching, 4 x HDMI® 2.0 inputs with 1 HDMI® 2.0 output, 12VDC power supply and mounting hardware included

4x1 Switcher

